

Heavy Duty Series



61 HD,
4" flange

X61 HD,
NPT vertical

61 HD and X61 HD, 1-10 BHP

NPT Vertical & Horizontal Flanged Discharge 1750 & 3450 RPM

ZOELLER 
ENGINEERED PRODUCTS

TRUSTED. TESTED. TOUGH.®

zoellerengineered.com

61 HD and X61 HD, 1-10 BHP

NPT Vertical & Horizontal Flanged Discharge 1750 & 3450 RPM

FEATURES*

- Multiple voltages available in 1 and 3 Phase
- 3" NPT vertical, 3" or 4" ANSI flange horizontal discharge
- 2-1/2" – 3" spherical solids capability
- Semi-open impeller
- 1750 or 3450 RPM
- Durable, epoxy coated cast iron construction
- Oil filled motor
- Dual mechanical shaft seals carbon/ceramic
- Buna-N elastomers
- 304 Stainless steel hardware
- 100% computerized water tested

OPTIONS*

- Seal upgrades
- Additional cord lengths
- Thermal sensors and moisture detection
- Viton elastomers

APPLICATIONS:

- Storm water removal
- Elevator sump
- Pumping stations
- Wastewater transfer
- Commercial wastewater solids handling

Tech Data Sheets	
1750 RPM	ZM1750
3450 RPM	ZM1752
Explosion Proof 1750 RPM	ZM2196
Explosion Proof 3450 RPM	ZM2206

*consult tech data sheet for specific technical information