

(X)7011, (X) 7012, (X) 7013 2 HP



TRUSTED. TESTED. TOUGH.®



(X)7011, (X)7012, (X)7013 2 HP

FEATURES*

- Multiple voltages available in 1 and 3 Phase
- 7011 & X7011 Reversing model
- 7012 & X7012 High head model
- 7013 & X7013 High flow model
- 1.25" NPT discharge
- Tri-slice® cutter design provides superior grinding with sharper cutting edges
- Cutting plate decreases solids to less than 1/8"
- Vortex impeller
- 3450 RPM
- Durable, epoxy coated cast iron construction
- Oil filled motor
- Dual mechanical shaft seals, upper carbon ceramic, lower silicon carbide/carbon
- Viton elastomers
- Moisture sensor detection
- Thermal overload (1 phase) or thermal sensor (3 phase and all X models)
- 304 Stainless steel hardware
- 100% computerized water tested

OPTIONS*

- Seal upgrades
- Additional cord lengths
- Certified performance audits
- Class 1 Division 1 Groups C & D explosion proof motor

APPLICATIONS:

- Sanitary sewage
- Housing developments
- Pressure sewers

Tech Data Sheets	
7011, 7012, & 7013	ZM1288
X7011, X7012, & X7013	ZM2595

^{*}consult tech data sheet for specific technical information