

Explosion Proof Commercial Duty

Dewatering,
Effluent & Sewage
Pumps 0.5 - 3.0 HP



ZOELLER 
ENGINEERED PRODUCTS

TRUSTED. TESTED. TOUGH.®

zoellerengineered.com

Explosion Proof Commercial Duty Dewatering, Effluent & Sewage Pumps 0.5 - 3.0 HP

FEATURES*

- Multiple voltages available in 1 and 3 Phase
- Class 1, Division 1, Groups C & D – Gas Areas
- Class 2, Division 1, Groups E, F & G – Dust Areas
- Durable, epoxy coated cast iron construction
- Oil filled explosion proof motor
- Dual mechanical shaft seals upper carbon/ceramic, lower silicon carbide/carbon
- Vortex impeller
- Viton gasket and O-rings
- SOW type power cord
- Moisture sensor detection
- Thermal overload switch (1 phase) or thermal sensor (3 phase)
- Stainless steel hardware and handle
- 100% computerized water tested

OPTIONS*

- Seal upgrades
- Additional cord lengths
- Certified performance audits

Discharge Sizes			
Effluent		Sewage	
X6160 Series	1.5", 2" or 3" NPT	X6280 Series	2" or 3" NPT
X6180 Series		X6290 Series	
		X6400 Series	4" ANSI Flange

APPLICATIONS:

- Commercial dewatering
- Automotive repair facilities sumps
- Septic tank effluent
- Low pressure effluent sewers
- Quick change oil stations

Tech Data Sheets			
Effluent		Sewage	
X6160 Series	ZM3382	X6280 Series	ZM1794
X6180 Series	ZM3384	X6290 Series	ZM3385
		X6400 Series	ZM3383

*consult tech data sheet for specific technical information