

- Longer battery life
- Friendlier design
- More compact and easy to install
- CSA approved



Reed Sensor Models 10-4011 APak® Standard 10-4013 APak® Z Control®



Mechanical Float Switch Models 10-4012 APak® Standard 10-4014 APak® Z Control®



Trusted. Tested. Tough.®



Features:

Standard Models

- NEMA 1 enclosure
- High water LED and alarm
- Low battery LED and alarm
- Silence/Reset button
- 87 decibel Alarm
- AC only mode, DC only mode, AC/DC mode
- Input screw terminals allow for versatility
- Long battery life (2 AA not included). Up to 2 years in AC/DC mode, up to 1 year in DC only mode.
- Power supply with 6' cord included
- 10-4011 comes with reed sensor
- 10-4012 comes with mechanical float switch

Features:

Z Control® Models

- All the Standard features plus:
- · 2nd Input for additional monitoring ability
- Dry contacts for connection to home security system, etc.
- Z Control Enabled!
 - Wifi equipped
 - Receive free text, email, and push alerts on:
 - Power outage
 - Low battery
 - Input 1 or 2 triggers
 - Loss of contact with Z Control®
 - Remotely Silence, Reset alarm.
 - Free Z Control App and Web interfaces
 - Free Z Control account
 - No monthly cost
 - Simple setup
 - Z Control connectivity LED
- 10-4013 comes with reed sensor
- 10-4014 comes with mechanical float switch
- 10-4683 comes with no switch





Notes:

Either the Standard or Wifi APak can be used to monitor nearly any switch or pair of dry contacts.

For sewage applications, the models with mechanical float switch are recommended (10-4012 and 10-4014).

If a direct wired alarm is required, use 91104-0001, APak Outdoor. with 15' mechanical float switch, OR 91104-0002, APak Outdoor with prewired 6' power cord and 20' mechanical float switch.

© Zoeller Co. All rights reserved.