# Z Control®



90002-0001

Connect Pivot<sup>®</sup> Pro and LPS control panels to the Z Control<sup>®</sup> Cloud.



## Wi-Fi Gateway



zoellerpumps.com | 800-928-7867 | 3649 Cane Run Rd., Louisville, KY 40211

# **Wi-Fi Gateway**

Use the Wi-Fi Gateway to connect your Zoeller product (Pivot Pro and LPS control panels) to the Z Control<sup>®</sup> Cloud in just a few simple steps. Connecting to Z Control<sup>®</sup> allows the user to gain remote access to control and manage devices and to receive email, text, and push alert notifications and reminders.

#### **Features:**

- Simple set-up
- Automatically pairs with connected device
- Compact design (3.5" x 2.5" x 1")
- Lower cost than previous model
- Free standard access. No additional charge or subscription needed for standard Z Control <sup>®</sup> account access
- Includes 3' Cat5 cable and hook and loop fasteners for mounting
- Nema 1 enclosure (additional protection required for outdoor use)
- Connectivity LED and Reset button



#### 🖉 Z Control Cloud

### ≮ Back

## Pivot Pro

Silence Alarms Reset Buzzer Test Share Device Delete Device

Status Alert History Device Settings Alert Settings Comment	5		
Pump 1	Last Updated: 12/7/2022 9:53:2	Last Updated: 12/7/2022 9:53:27 AM	
✓ Ready	Device Name	Pivot p	
Alarms Okay	Device Type	Pivot P	
✓ Pump 2 ✓ Next To Run	Device ID	2ATIED	
✓ Alarms Okay	Firmware Version	1.4	
V HOA 1	IP Address	192.168	
✓ Auto	Circuit Board Temperature	89.6 F*	
✓ HOA 2	Panel Operation Time	70 Days,	
✓ Auto	System Time Since Last Reset	8 Days, 8	
<ul> <li>Inputs</li> <li>✓ Stop Float</li> </ul>	Reset Count	194	
	Last Reset Cause	Startup	
	High Water Float Count	1	
	Run Mode	Duplex	
	Lead/Lag Select	Ratio	
	Lead/Lag Ratio	1:1	
	Pump 1 Cycle Count	12	
	Pump 1 Elapsed Run Time	39 Mins	
	Pump 1 Last Cycle Duration	8 Secs	
	Pump 2 Cycle Count	12	
	Pump 2 Elapsed Run Time	5 Mins	
	Pump 2 Last Cycle Duration	5 Secs	

#### **Benefits To User:**

- Manage pump stations from your mobile device
- Supervise Pivot Pro and LPS control panels
- Remotely view cycle counts, elapsed time, pump modes and settings
- Change certain settings via mobile app or website.
- Silence active alarms, reset certain conditions
- Set up email, text, and push notifications for alarms and reminders

FM3393 0123 Supersedes 1121

**A** CAUTION All installation of controls, protection devices and wiring should be done by a qualified licensed electrician. All electrical and safety codes should be followed including the most recent National Electrical Code (NEC) and the Occupational Safety and Health Act (OSHA).