

(X)7011, (X) 7013 2 HP



TRUSTED. TESTED. TOUGH.®



## (X)7011, (X)7013 2 HP

## **FEATURES\***

- Multiple voltages available in 1 and 3 Phase
- 7011 & X7011 Reversing
- 7013 & X7013 Single direction
- 1.25" NPT vertical or horizontal discharge
- Tri-slice® cutter design provides superior grinding with sharper cutting edges
- Cutting plate decreases solids to less than 1/8"
- Vortex impeller
- 3450 RPM
- Durable, epoxy coated cast iron construction
- Oil filled motor
- Dual mechanical shaft seals, upper carbon ceramic, lower silicon carbide/carbon
- Viton elastomers
- Moisture sensor detection
- Thermal overload (1 phase) or thermal sensor (3 phase and all X models)
- 304 Stainless steel hardware
- 100% computerized water tested

## **OPTIONS\***

- Seal upgrades
- Additional cord lengths
- Certified performance audits
- Class 1 Division 1 Groups C & D explosion proof motor

## **APPLICATIONS:**

- Sanitary sewage
- Housing developments
- Pressure sewers

\*consult tech data sheet for specific technical information

Tech Data Sheets	
7011, 7013	ZM1288
X7011, X7013	ZM2595