





71 and 72 Heavy Duty Grinder Pumps

ZM3356 0823 Supersedes 0222

3 - 15 HP, 3450 RPM Flanged Discharge New Cutter Assembly For Improved Reliability

71 HD FEATURES*

- Multiple voltages available in 1 and 3 Phase
- 2" NPT vertical, 2.5-3" ANSI flange horizontal discharge
- Cutting plate decreases solids to less than 1/4"
- Vortex impeller
- 3450 RPM
- Durable, epoxy coated cast iron construction
- Oil filled motor
- Dual mechanical shaft seals: Upper -Carbon Ceramic, Lower - Silicon Carbide/ Silicon CarbideBuna-N elastomers
- Thermal Sensor and moisture detection
- 304 Stainless steel hardware
- 100% computerized water tested

OPTIONS*

- Seal upgrades
- Additional cord lengths
- Viton elastomers
- Trimmed or bronze impeller
- Certified performance audits
- Explosion proof motors

Tech Data Sheets	
71 HD	ZM1766
72 HD	ZM3316

72 HD FEATURES*

- 200, 230, 460 & 575 Volt 3 phase
- 3" or 4" ANSI flange horizontal discharge
- Cutting plate decreases solids to less than 1/4"
- Vortex impeller
- 3450 RPM
- Durable, epoxy coated cast iron construction
- Oil filled motor
- Dual mechanical shaft seals: Upper -Carbon Ceramic, Lower - Silicon Carbide/ Silicon CarbideBuna-N elastomers
- Thermal Sensor and moisture detection
- 304 Stainless steel hardware
- 100% computerized water tested

OPTIONS*

- Seal upgrades
- Additional cord lengths
- Viton elastomers
- Trimmed impeller
- Certified performance audits

APPLICATIONS

- Sewage lift stations
- Housing developments
- Pressure sewers
- Pumping station

^{*}consult pumps tech data sheets for specific technical information