



Effluent Vertical Turbine

Short set and deep well applications
7" - 16" Bowl Size

ZOELLER 
ENGINEERED PRODUCTS

TRUSTED. TESTED. TOUGH.®

zoellerengineered.com

Effluent Vertical Turbine

Short set and deep well applications; 7" - 16" Bowl Size

Features

- Customized, precision pump solutions
- Stainless steel bolting
- Flanged or threaded discharge
- Customizable column, tube and shaft adaptations
- Bronze/ss sand collar to deter abrasives from entering bearing and motor bracket bearing
- Impeller collet of stainless steel to provide a positive lock of impeller to pump shaft
- Silicon bronze or 316SS enclosed impeller, balanced and machined for high efficiency
- Extra heavy close grain cast iron bowl with hydraulic surfaces enameled for high efficiency and resistance against abrasive conditions
- Personal attention and quick shipping from 1 - 2 days
- Pump testing includes (optional adder)
 - Witness or non-witness performance testing
 - Hydro-static testing

Options

- Customizable
- Shaft seal, and bushing upgrades
- Ductile iron close grain bowls for high pressure
- Fabricated discharge
- 316SS FLG pipe & Fab head
- Custom wear rings
- Flanged motor coupling for VSS motors
- 316SS bowls investment casset - select models

Applications

- Municipal
- Industrial
- Commercial
- Dewatering
- Fresh water
- Treated waste water
- Effluent water
- Pressure booster pumps
- Lift stations

Quoting

Fill out ZM3333

Email to: zepvt@wolfpumps.com



MAIL TO: P.O. BOX 16347 • Louisville, KY 40256-0347
SHIP TO: 3649 Cane Run Road • Louisville, KY 40211-1961
Tel: (502) 778-2731 • 1 (800) 928-PUMP

Trusted. Tested. Tough.®

visit our web site:
zoellerengineered.com